



English Find Authorized Distributors Contact Us About Littelfuse Partner Login

Search All Search by Keyword, Part Number, Certification Number etc. Search

PRODUCTS INDUSTRIES SERVICES TECHNICAL RESOURCES Competitor Cross Reference Order Sample Check Distributor Stock

Home > Products > DC Solenoids and Relays > Normally Open Relays <100 Amps > Continuous Duty SPST Relays > 24063

Print

24063 - 24V Insulated Continuous Duty SPST Solenoid

Series: Continuous Duty SPST Relays

Questions? Contact Littelfuse Support



24V insulated Normally Open Contacts, SPST, One circuit: Off - On. 85A.
 Housing: Plated steel.
 Large terminals: Copper 5/16" -24 thread, hexnuts and lockwashers included.
 Coil, ignition and ground terminals: Steel 10-32 thread, hexnuts and lockwashers included.
 Bracket mounting holes 5/16" x 19/32" (7.9 x 15.1) on 2 13/64" centers (56.0mm).



Specifications

Property (Mouseover for details)	Value
Description	Continuous Duty Solenoid
Special applications	Universal
Insulated/Grounded	Insulated
NO/NC	normally open
Circuitry	SPDT
Contacts	copper
Housing	plated steel
Voltage rating	24V
Terminals	copper; 10-32 thread and 5/16"-24 thread. Hex nuts and lock washers included
Continuous current	85A/35A
Bracket	Straight
Bracket mounting	Holes 5/16" x 19/32", 2-13/64" on center
UL Marine & CE ISO 8846 Marine	Not listed

Connect with Littelfuse

Sign up to receive special offers and news

Enter your email Submit

For more details about how we use your information, check our [Privacy Statement](#).



About Littelfuse

- Capabilities Brochures
- About Littelfuse
- History
- Investor Relations
- Legal
- Press Room
- Privacy Statement
- Website Feedback

Explore Littelfuse

- Careers
- Check Distributor Stock
- Competitor Cross Reference
- Industries
- Order Samples
- Products
- Services

Technical Resources

- Application Designs
- Education
- FAQs
- Littelfuse University
- Product Catalogs
- Quality Documents
- Technical Documents

